



G-21 SERIES

DIMENSION

G-21N, G-21P / G-21N-QD, G-21P-QD



G-21R, G-21R-QD



QD PINOUT

*3 wire QD wiring



*2 wire QD wiring



*2 wire EQD wiring



SPECIFICATION


TYPE	G-21R	G-21N	G-21P
CONNECT DIAGRAM			
CHARACTERISTICS			
WIRING METHOD	2-Wire Type	3-Wire Type	
SWITCHING LOGIC	SPST, Normally Open	Solid State Output, Normally Open	
SENSOR TYPE	Reed Switch	NPN Current Sinking	PNP Current Sourcing
OPERATING VOLTAGE	5~240V DC/AC	5~30V DC	
SWITCHING CURRENT	100 mA max.	200 mA max.	
CONTACT RATING	10 W max.	6 W max.	
CURRENT CONSUMPTION	—	15 mA @ 24V max. (Switch Active)	
VOLTAGE DROP	3.5 V max.	1.5 V max.	
LEAKAGE CURRENT	—	0.01 mA max.	
INDICATOR	Green LED	Red LED	Green LED
CABLE	φ 4 , 2C , PVC	φ 4 , 3C , PVC	
OPERATING FREQUENCY	200 Hz	1000 Hz	
MAGNET REQUIREMENT(NOTE 1.)	60 Gauss		
TEMPERATURE RANGE	-10~70 ℃		
SHOCK(NOTE 2.)	30 G	50 G	
VIBRATION (NOTE 3.)	9 G		
ENCLOSURE CLASSIFICATION	IEC 529 IP 67		
PROTECTION CIRCUIT	None	Reverse Polarity, short-circuit	

NOTE : 1.Measuring standard target : φ15.5 × φ8 × 5t (Anisotropy Rubber Magnet)

2.Sin Wave / X · Y · Z 3 Directions / 3 Times Each Direction / 11ms Each Time.

3.Double Amplitude 1.5mm / 10Hz-55Hz-10Hz (Sweep 1min) / X · Y · Z 3 Directions / 1 Hour Each Time.

MOUNTING CLAMPS



GENTLE AUTOMATIC SOLUTION SDN BHD (684637-U)

No.36, Jalan Industri USJ 1/13, Taman Perindustrian USJ 1, 47600 Subang Jaya, Selangor, Malaysia

Tel: 603-8023 7743 / 8743 Fax: 603-8023 9743 <http://www.gentle.com.my> email: sales@gentle.com.my